



World's Best Graffiti Coating

An extremely DURABLE and LONG LASTING, PROTECTIVE coating for brick, stone, masonry, timber and natural building surfaces

Product Data Sheet

Product Code: WB0070

Issued: August 8, 2016

PRODUCT DESCRIPTION

World's Best Graffiti Coating (WBGC) is a water based all-weather, long-term SACRIFICIAL protection, formulated for most types of surfaces. Provides durable protection against spray paint, marker / felt tip pens pollution and grime. Also provides protection against salt and sea type moisture.

Correctly applied, life expectancy against graffiti is generally 7 years but it can be effective up to 10 years.

This protective coating is permeable and allows the surface to breath. Prevents graffiti from penetrating into the substrate.

The surface must be re-protected following graffiti removal which can be done immediately to a damp (not wet) surface.


WBGC is readily biodegradable according to OECD test 302 B.




Historic Buildings




Decorative Sound Walls




Feature Walls



Wooden Fences



Split Face / Cinderblock



Natural Stone

FEATURES & BENEFITS

- Safe, quick and easy to apply by spray, brush or roller.
- Fast drying time.
- Makes getting graffiti off walls a pleasure.
- Virtually invisible / matte finish



Urban Restoration Group US Inc. (URG US INC) maintains Safety Data Sheets (SDS) on all of its products. These sheets contain information that you may need to protect your employees and customers against health or safety hazards associated with our product. URG US INC recommends that you obtain a copy of the respective SDS sheet prior to using or transporting our products. The information in this Product Data Sheet is based on data we believe to be reliable. It is offered in good faith, but without guarantee, as ultimately the conditions and methods of the use of our products are beyond our control.

URBAN RESTORATION GROUP US INC MAIL: 1146 N Central Ave. #531, Glendale CA 91202 USA. WAREHOUSE: 5439 San Fernando Rd. W, Los Angeles CA 90039 USA. TEL: 1-818-247-2555. FAX: 1-818-247-2515. EMAIL: sales@graffitiremovalinc.com. WEB: www.graffitiremovalinc.com



FEATURES & BENEFITS cont...

- Non toxic and virtually odorless.
- Ideal for heritage buildings.
- Can be used on porous and non porous substrates.

INSTRUCTIONS FOR USE

Preparation

Clean off both graffiti and other contamination, such as road grime, grease, wax, oil and paint residue etc. from substrate.

It is normal best practice to mask and protect windows in a suitable manner.

Exterior Protection

Shake or stir product well prior to use. WBGC can be applied with any of the following: rollers, paint brush, low-pressure sprayer or airless sprayer. Two coats are usually applied.

NOTE: Allow some intermediate drying between coats.

WBGC can be applied to a damp, not wet surface. Runs and/or excessive application can easily be washed off with water, following completion of work.

**FOR EXPERT TECHNICAL ADVICE ON YOUR JOB,
PLEASE CALL 1-818-247-2555 OR
EMAIL SALES@GRAFFITIREMOVALINC.COM**



World's Best Graffiti Coating

An extremely DURABLE and LONG LASTING, PROTECTIVE coating for brick, stone, masonry, timber and natural building surfaces


Product Data Sheet

Product Code: WB0070


Issued: August 8, 2016



Handheld Pump-up Sprayer



High Volume Low Pressure Sprayer (HVLP)



Airless Sprayer

Interior Protection

Some painted substrates can be protected using a roller or with a low-pressure spray in combination with a brush or roller. The protection is applied three times.

APPLICATION

Use the product as provided. Do not dilute. Walls can be dampened during hot weather to assist application.

This product information is intended as a guide for use of this product. Urban Restoration Group US Inc. cannot give any guarantee for end result achieved. The applicator of the product shall carry out testing and be responsible for the result.

COVERAGE GUIDELINES

Varies dependent upon the porosity of surface material.

- Concrete, brick or similar: 500 sq ft per gal per coat.
- Sandstone, plaster or other soft absorbent surfaces: 360 sq ft per gal per coat.
- Painted surfaces, 640 sq ft per gal per coat

2 coats are recommended.

Drying Period

The protected surface will be water and graffiti-resistant after 2 hours and dry after 4 hours. Ultimate protection will be achieved after 72 hours.

Appearance on surface

Transparent, mostly invisible dependent on type of surface. UV-resistant. Weather / water / graffiti resistant.

Before commencing large scale use always test first to ensure finish is satisfactory. Some building materials could darken or become shiny.

EXTERIOR GRAFFITI REMOVAL

Method 1: Normal substrate.


Remove graffiti with hot water and high pressure (~ 90°C / 200°F & 90-50 bar / 1300-2175 psi). For faster removal, use World's Best Graffiti Removers in conventional manner. Re-protect cleaned area.




Filled-in bubble writing on previously coated masonry wall.



Graffiti is removed using just hot water at 2000 PSI / 2-3 gal per minute.



Blue spraycan on pre-coated random wall. Brush on BBSM.



Rinse with cold water.



Once clean, re-apply WBGC.

INTERIOR GRAFFITI REMOVAL

Removal from Painted Substrate

Brush on SENSITIVE SURFACE REMOVER to small areas at a time and wipe off with a damp cloth completing each area before proceeding further. Re-apply WORLD'S BEST COATING.



Urban Restoration Group US Inc. (URG US INC) maintains Safety Data Sheets (SDS) on all of its products. These sheets contain information that you may need to protect your employees and customers against health or safety hazards associated with our product. URG US INC recommends that you obtain a copy of the respective SDS sheet prior to using or transporting our products. The information in this Product Data Sheet is based on data we believe to be reliable. It is offered in good faith, but without guarantee, as ultimately the conditions and methods of the use of our products are beyond our control.

URBAN RESTORATION GROUP US INC MAIL: 1146 N Central Ave. #531, Glendale CA 91202 USA. WAREHOUSE: 5439 San Fernando Rd. W, Los Angeles CA 90039 USA. TEL: 1-818-247-2555. FAX: 1-818-247-2515. EMAIL: sales@graffitiremovalinc.com. WEB: www.graffitiremovalinc.com



World's Best Graffiti Coating

An extremely DURABLE and LONG LASTING, PROTECTIVE coating for brick, stone, masonry, timber and natural building surfaces

Product Data Sheet

Product Code: WB0070

Issued: August 8, 2016

INTERIOR GRAFFITI REMOVAL cont...

Removal from Porous Substrate

Apply SENSITIVE SURFACE REMOVER. Rinse off with hot water and wet-vac.

Re-protection of Cleaned Surface

When removing graffiti, the protective coating is also normally removed. Re-apply 2 coats of WBGC.

TEMPERATURE USAGE

Ideal temperature for external application should be between 45°-95°F / 8°-35°C. Minimum temperature is 40°F

Relative humidity must not exceed 95%.

NB: Fresh concrete has to cure for at least 28 days before protection.

TECHNICAL DATA

Composition

Water carried paraffin wax dispersion.

5-10% solid contents.

Properties

Color: White.

Odor: Odorless.

PH: 8

Storage: Store in a frost-free environment in original container.

Shelf Life: Approximately 3 years.

Precaution: Use protective clothing and gloves.

DOT Markings: Not classified as dangerous.

See SDS for further information.

CONTACT MANUFACTURER

Urban Restoration Group US Inc.

5439 San Fernando Rd. W., Los Angeles CA 90039 USA

Tel: +1-818-247-2555. Fax: +1-818-247-2515

Email: sales@graffitiremovalinc.com

Web: www.graffitiremovalinc.com



Urban Restoration Group US Inc. (URG US INC) maintains Safety Data Sheets (SDS) on all of its products. These sheets contain information that you may need to protect your employees and customers against health or safety hazards associated with our product. URG US INC recommends that you obtain a copy of the respective SDS sheet prior to using or transporting our products. The information in this Product Data Sheet is based on data we believe to be reliable. It is offered in good faith, but without guarantee, as ultimately the conditions and methods of the use of our products are beyond our control.

URBAN RESTORATION GROUP US INC MAIL: 1146 N Central Ave. #531, Glendale CA 91202 USA. WAREHOUSE: 5439 San Fernando Rd. W, Los Angeles CA 90039 USA. TEL: 1-818-247-2555. FAX: 1-818-247-2515. EMAIL: sales@graffitiremovalinc.com. WEB: www.graffitiremovalinc.com